

Bus Rapid Transit for Greater Kampala Ministry of Works & Transport





Eric Trel
Project

Manager


UN-Habitat

Governing

Council

Nairobi
April 2013

Main challenge



Kampala population growth 5.7% per year = 660 per day

Transport need
Congestion
Greenhouse Gases

Maximum capacity per lane per hour: 800 vehicles, or 9,000 bus passengers

Bus Rapid Transit




Photo: ITDP

- High-frequent mass transport
- Large buses
- Separate bus lanes


- Fast, attractive & safe
- Affordable
- Low investment
- Quick realisation

154 Cities with Bus Rapid Transit










BRT for Greater Kampala: main characteristics


- High capacity vehicles: 18m long articulated, low floor buses
- High frequency: up to 60 vehicles per hour (each way).
- High operating speed 30 km/h to minimise need for subsidy.



Traffic management

- Complete redesign of the right-of-way
- Separate bays for parking, loading & unloading
- Key junctions: traffic lights and separate lane for right-turns
- Introduce one-way traffic in the city centre





Implementation

- Infrastructure: USD 8 million per kilometre (including stations and systems, excluding land acquisition and fleet).
- Fleet: to be provided and financed by the Operator.
- Realisation in 5 years: from feasibility study 2012 to start operation in 2017.
- Key to success: a Transport Authority or BRT Agency for realising the project and managing the operation.
- Result: approximately 300,000 passengers per day.